

# SIRIUS

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET  
Gres porcellanato colorato in massa - Fully-coloured porcelain tiles

**POLIS**  
CERAMICHE  
DATA - DATE: 9 MARZO 2022  
VERS. 02

## DATI GENERALI - GENERAL DATA

SERIE-SERIES :	<b>SIRIUS</b>
FORMATI-SIZES :	<b>60X120 - 60X60 - 30X60</b>
NOMI-NAMES :	<b>POLARIS - CASTOR - VEGA - ANTARES</b>
COLORI-COLOURS :	<b>BIANCO - GRIGIO CHIARO - GRIGIO - ANTRACITE</b> <b>WHITE - LIGHT GREY - GREY - DARK GREY</b>
SUPERFICIE-SURFACE :	<b>MAT</b>
NR. COLORI-NR. COLOURS :	<b>4</b>










## ACCESSORI - ACCESSORIES

FONDI-TILES :	<b>X</b>	BATTISCOPIA-BULLNOSE:	<b>X</b>
DECORI-DECORS :	<b>X</b>	GRADINO-STEP:	<b>X</b>

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno  
Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

## CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)  
Appendice G - Classe di appartenenza **B1a** - Class of **B1a**

RESISTENZA AL GELO FROST RESISTANCE		<b>SI</b>	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		<b>7</b>	UNI EN 101
RESISTENZA ALL'ABRASIONE RESISTANCE TO DEEP ABRASION		<b>≤ 175 mm<sup>3</sup></b>	EN ISO 10545-6
SPESSORE IN BASE AL FORMATO THICKNESS IN REFERENCE TO THE SIZES		<b>9 mm</b>	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		<b>R 10</b>	DIN 51130
		<b>A+B</b>	DIN 51097
		<b>&gt;μ 0,40</b> Attrito soddisfacente Acceptable Friction	D.M.236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		<b>5</b>	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		<b>A-LA-HA</b>	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE/MODULO DI ROTTURA BENDING STRENGTH/BREAKING STRENGTH		<b>≥ 35 N/mm<sup>2</sup></b>	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		<b>≤ 0,5%</b>	EN ISO 10545-3